

# DNS of Turbulence Flow over a Confined Wavy Channel

蔡永培, 周中祺

Mechanical Engineering

Engineering

yptsai@chu.edu.tw

## Abstract

Fluid flowing over a smooth boundary of a channel creates turbulence if the velocity is large enough. The relationship of the Reynolds shear stress to the structure of turbulence is the basic mechanism interested. Less attention has been given to flow over rough or structured surface. Turbulent flow over a wavy surface displays characteristics that are not found in flow over a flat surface. The mean and statistical quantities of a fully developed turbulent flow in a channel with a sinusoidal bottom wall (with wavelength  $\lambda$ ) and a flat top wall have been a interesting research topic for a long time. Several researchers used Laser Doppler Velocimetry (LDV) to measure the velocity field to study the influence of wave steepness on the flow pattern. Particle image velocity (PIV) has been used to examine the spatial variation of the velocity in different planes of the flow through a water channel. Balasubramanian et al. solved the time-averaged Navier-Stokes equations using spectral method for laminar and turbulent flow over large amplitude waves. They explored both  $k-\epsilon$  model and an algebraic model. The main uncertainty in the numerical results lies in the closure models for the Reynolds stresses. Extensive measurements of the Reynolds stresses are obtained by Hudson. The experiments done by Kuzan and Thorsness are at lower Reynolds numbers. In the last twenty years, direct numerical simulation (DNS) has become a valuable method in providing a theoretical understanding of turbulent flows. In DNS, the Reynolds stresses are not modeled. The velocity field is simulated by solving the Navier-Stokes equations directly. DNS is used to study turbulent flows at low or moderate Reynolds numbers because the spatial resolution required increases as the Reynolds number increases. This is a constrain. In this paper the results of direct numerical simulation of the flow over a wavy wall are presented. Two-dimensional Navier-Stokes equations are solved using WENO scheme which is an

essentially non-oscillatory scheme with high resolution for multi-dimensional hyperbolic system of conservation laws. A structured surface, which consists of a train of sinusoidal waves with different height to length ratio ( $2a/\lambda$ ) at values of 0.05 and 0.10 were used as the bottom wall of a rectangular channel with a half-height,  $h$ , of 25mm, and a width of 200mm. The evolution in space and time of fluid particles in this flow configuration are examined. Turbulence intensities, Reynolds stresses, turbulent energy production, instantaneous and mean flow field, and the pressure distribution of the turbulent channel flow with a wavy wall are calculated and investigated. A physical understanding of the structure of turbulent field would be greatly enhanced if information about the spatial variation of Reynolds stress is available. The purpose of this research is to obtain systematic structural information about the turbulent flow field. Features of the turbulence structure are discussed.

Keyword : DNS, Navier-Stokes equations, WENO scheme, Confined Wavy Channel